

Cuemaker	Total Butt Length	Forearm Length	Joint Diameter	Forearm/Handle Diameter	Forearm/Handle Bolt type & length	Handle Length	Butt Sleeve Length	Left Sleeve Length	Right Sleeve Length	Butt Cap Length	Butt Cap End I.D.	Joint Pin	Rubber Bumper	Remarks
Samsara	737 mm	298 mm	21.4 mm	25.36 mm	3/8 x 16 x 125 mm, forearm tenon	325 mm	89 mm	30.34 mm	31.57 mm	25.4 mm	31.86 mm	Atlas Uni-Lok 84 mm / White Phenolic	Button type, slip	Adjustable 1/2 in. weight bolt, 73 mm hole
Meucci	735 mm	291 mm	21.02 mm	25.08 mm	5/16 x 18 x 80 mm, forearm tenon	338 mm	69 mm	30.80 mm	32.27 mm	37 mm	32.5 mm	5/16 x 18 x 77mm / black linen	Flat type slip-o	5 inch adj weight bolt, finished wrap, 140 mm
Gina	734 mm	314 mm	21.32 mm	27 mm	3/8 x 16 x 71 mm, forearm tenon	299 mm	83 mm	30.92 mm	31.58 mm	38 mm	31.71 mm	5/16 x 18 x 72.5 mm / ivory	Proprietary	Adjustable weight bolt, 35 mm hole
R. Black	728 mm	297 mm	21.18 mm	26.93 mm	3/8 x 8 x 103 mm, forearm tenon with buzz ring	317 mm	76 mm	31.38 mm	32.22 mm	38 mm	32.67 mm	5/16 x 14 x 83 mm / stainless steel	3/4in. x 3/4in. v	Adjustable weight bolt, 125 mm hole
Tiad	735 mm	296 mm	21.22 mm	26.68 mm	3/8 x 16 x 107 mm, forearm tenon	322 mm	75 mm	30.32 mm	31.44 mm	42 mm	31.61 mm	5/16 x 18 x 71.5 mm / stainless steel	1/2in. x 3/4in. v	Fixed weight
Schon	736 mm	315 mm	21.23 mm	26.92 mm	3/8 x 10 x 84 mm, forearm tenon	308 mm	82.5 mm	30.89 mm	32.31 mm	30.5 mm	32.47 mm	5/16 x 14 x 85 mm / stainless steel	lin. x 1 in with	Adjustable weight bolt, 97 mm hole
Schick	737 mm	310 mm	21.51 mm	26.50 mm	3/8 x 10 x 103 mm, forearm tenon	315 mm	90 mm	31.55 mm	32.93 mm	21 mm	33 mm	3/8 x 10 x 87 mm / ivory	lin. X 1/2in. w	Adjustable weight bolt, 80 mm hole
Omega DPK	735 mm	305 mm	20.92 mm	27.41 mm	3/4 x 26 x 77 mm, phenolic tenon	305mm	111 mm	31.44 mm	32.09 mm	14mm	32.18mm / 32.2	3/8 x 14 x 66 mm/black linen	Flat type slip-o	Adjustable weight bolt, 104 mm hole
Southwest JF	730 mm	305 mm	21.15 mm	26.88 mm	3/8 x 16 x 69 mm, handle tenon	300 mm	116 mm	30.78 mm	31.68 mm	9 mm	31.69 mm	3/8 x 11 x 65 mm(brass) / black linen	Flat type slip-o	hidden weight bolt, 116 mm hole
Mc Worter	735 mm	303 mm	21.08 mm	26.76 mm	3/8 x 10 x 82 mm, forearm tenon	306 mm	114 mm	30.65 mm	32.50 mm	11 mm	32.42 mm	3/8 x 10 x 78 mm/black linen	Button screw ty	Fixed weight
PFD	736 mm	304 mm	21.38 mm	25.47 mm	handle cored into forearm	318 mm	96 mm	29.94 mm	31.77 mm	19 mm	31.92 mm	Atlas Uni-Lok 82.5 mm/ stainless steel	Flat type slip-o	Adjustable weight bolt, 65 mm hole
Jacoby	736 mm	323 mm	21.43 mm	24.86 mm	3/8 x 16 x 63 mm, handle tenon	304 mm	93 mm	29.63 mm	31.57 mm	16 mm	31.90 mm	5/16 x 14 x 71 mm/ stainless steel	Button screw ty	Adjustable weight bolt, 210 mm hole
Huebler	738 mm	293 mm	21.31 mm	25.94 mm	3/8 x 16 x 102, handle tenon	331 mm	82 mm	30.23 mm	31.18 mm	32 mm	31.37 mm	5/16 x 18 x 65.5 mm / ivory	lin. X 1/2in. w	Adjustable weight bolt, 108 mm hole
Seruggs	738.5 mm	306 mm	21.25 mm	25.65 mm	3/8 x 16 x 78 mm, forearm tenon	317.5 mm	77 mm	30.80 mm	38 mm	31.70 mm	32.05 mm	5/16 x 14 x 78 mm / stainless steel	lin. X 1/2in. w	Adjustable weight bolt, 133 mm hole
Judd	737 mm	313 mm	21.23 mm	25.58 mm	3/8 x 16 x 81 mm, forearm tenon	312 mm	80 mm	30 mm	31.42 mm	32 mm	31.66 mm	3/8 x 10 x 84 mm / Brown phenolic	lin. X 1/2in. w	adjustable weight bolt, 80 mm hole
Weston	737 mm	315 mm	21.95 mm	26.34 mm	5/8 x 12 x 50mm wooden tenon	301 mm	88.5 mm	29.37 mm	29.65 mm	32.5 mm	29.86 / 34.13 in	5/16 x 14 x 77.5/ stainless steel, Piloted	lin. X 1/2in. w	Adjustable weight bolt, 120 mm hole
Schrager	727 mm	305 mm	21.81 mm	25.86 mm	3/8 x 10 x 80 mm, forearm tenon	304 mm	90 mm	30.89 mm	31.44 mm	28 mm	31.27 mm	3/8 x 10 x 107 mm / White Phenolic	Button screw ty	Fixed weight
Bludworth	735 mm	312 mm	21.25 mm	26.17 mm	3/8 x 10.33 x 50 mm, handle tenon into buzz ring	309 mm	99 mm	30.85 mm	31.52 mm	15 mm	31.52 mm	3/8 x 10.33 x 61.5 mm/ black linen	lin. X 1/2in. w	Adjustable weight bolt, 75 mm hole
Buss	733 mm	305 mm	21.06 mm	26.38 mm	3/8 x 10 x 74 mm, 3 1/4 handle tenon	318.5 mm	91.5 mm	31.36 mm	33.20 mm	18 mm	33.33 mm	3/8 x 10 x 72 mm/ black linen	lin. X 1/2in. W	Adjustable weight bolt, 160 mm hole
Joss	737 mm	305 mm	21.21 mm	26.13 mm	see Black boar	330 mm	89.5 mm	30.92 mm	32.72 mm	12.5 mm	32.61 mm	5/16 x 14 x 78 mm/ stainless steel	Flat screw type	Adjustable weight bolt, 180 mm hole
Robinson	737 mm	322.5 mm	21.05 mm	26.86 mm	5/16 x 18 x 112 mm, forearm tenon	300 mm	89 mm	29.54 mm	29.57 mm	25.5 mm	29.52 mm	5/16 x 18 x 108mm Bolt in Shaft/resin on	lin. X 1/2in. W	Adjustable weight bolt, 57 mm hole
Porper	735 mm	303.5 mm	21.44 mm	26.81 mm	3/8 x 10 x 80 mm, forearm tenon	312.5 mm	98 mm	31.31 mm	32.42 mm	21 mm	32.56 mm	3/8 x 10 x 74 mm / Ivory	Button screw ty	Adjustable weight bolt, 168 mm hole
Martinez	735 mm	310 mm	21.26 mm	26.14 mm	3/8 x 16 x 131.5 mm, handle tenon	311 mm	89 mm	31.28 mm	32.41 mm	25 mm	32.47 mm	3/8 x 12 x 78 mm / black linen	Home made oc	Adj weight bolt, chamfered octagon end, 128 mm
Ned Morris	736.5 mm	311 mm	21.43 mm	25.08 mm	1/2 x 14 x 80 mm, forearm tenon	304 mm	84.5 mm	29.91 mm	30.28 mm	37 mm	30.69 mm	3/8 x 10 x 77 mm/black linen	lin. X 1/2in. W	adjustable weight bolt, 176 mm hole
Mottey	736 mm	318 mm	21.37 mm	26.49 mm	3/8x 10 x 78 mm, handle tenon	306 mm	93 mm	30.98 mm	32.76 mm	19 mm	32.83 mm	3/8 x 7.5 x 91.5 mm / black linen	lin. x 1 in with	Adjustable weight bolt, 77 mm hole
Andresen	733 mm	302 mm	22.10 mm	26.03 mm	3/8x 10pri x 120 mm, no tenon	295.5 mm	103 mm	30.58 mm	31.54 mm	32.5	31.83 mm	3/8 x 11 x 94 mm/ White Phenolic	lin. X 1/2in. W	Fixed weight
Capone	737.5 mm	310.25 mm	21.39 mm	27.43 mm	5/16 x 14 x 104 mm, handle tenon	385 mm	32.25 mm	32.06 mm	32.57 mm	10 mm	32.71 mm	3/8 x 7.5 x 91 mm/ Ivory	Flat type slip-o	Adjustable weight bolt, 80 mm hole
Black Boar	736 mm	307 mm	21.24 mm	26.57 mm	none, straight to butt sleeve	306.5 mm	74.5 mm	31.12 mm	31.92 mm	38	32.07 mm	5/16 x 14 x 78 mm/ stainless steel	lin. X 1/2in. W	Adjustable weight bolt, 90 mm hole
Schuler	737 mm	329 mm	22.01	27.78 mm	5/16 x 14 x 45 into aluminum sleeve	289.5 mm	80.5 mm	30.49 mm	30.90 mm	38 mm	30.39 mm	5/16 x 14 x 46mm / White Phenolic, deep	lin. X 1/2in. W	Washer type weight adjustable, 70 mm hole
M. Bender	737 mm	305 mm	21.53 mm	27.20 mm	threaded wood and tenon, 50 mm	305mm	109 mm	31 mm	31.12 mm	19 mm	31.17 mm	3/8 x 14x 78 mm / black linen	Flat type slip-o	Adjustable weight bolt, 75 mm hole