



## Material Safety Data Sheet

Copyright, 2007, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M(TM) Scotch-Weld(TM) Neoprene Contact Adhesive 10, Neutral Brushable

**MANUFACTURER:** 3M

**DIVISION:** Industrial Adhesives and Tapes Division

**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 04/09/2007

**Supersedes Date:** 06/07/2003

**Document Group:** 10-2685-5

#### Product Use:

Limitations on Use: not for retail sale or household use  
Specific Use: contact adhesive  
Intended Use: Industrial use

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
Polychloroprene	9010-98-4	10 - 30
Petroleum Distillate	64741-84-0	10 - 30
n-Hexane	110-54-3	10 - 30
Toluene	108-88-3	10 - 30
Acetone	67-64-1	10 - 30
Magnesium Resinate	68611-24-5	7 - 13
Cyclohexane	110-82-7	1 - 5
Zinc Oxide	1314-13-2	0.1 - 1

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Odor, Color, Grade:** yellow, solvent odor.

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and

flash back. May cause severe eye irritation.  
cause birth defects or other reproductive harm.

May cause target organ effects. Contains a chemical or chemicals which can

## 3.2 POTENTIAL HEALTH EFFECTS

### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

### Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

May be absorbed through skin and cause target organ effects.

### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Prolonged or repeated exposure may cause:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

May be absorbed following inhalation and cause target organ effects.

### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

### Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

<b>Autoignition temperature</b>	465 °C [ <i>Details:</i> Acetone]
<b>Flash Point</b>	-4 °F [ <i>Test Method:</i> Closed Cup] [ <i>Details:</i> Acetone]
<b>Flammable Limits - LEL</b>	1.0 % volume
<b>Flammable Limits - UEL</b>	12.8 % volume
<b>OSHA Flammability Classification:</b>	Class IB Flammable Liquid

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to

disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with detergent and water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Contents may be under pressure, open carefully. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Ground containers securely when transferring contents. Wear low static or properly grounded shoes. Avoid breathing of vapors, mists or spray. Avoid static discharge. Avoid eye contact with vapors, mists, or spray. Vapors may ignite explosively. May cause flash fire. Prevent build-up of vapors - open all windows and doors. Maintain vapor concentrations below recommended exposure limits. Use only with cross-ventilation. Without adequate ventilation, vapors may settle in low-lying areas. Keep away from heat, sparks, and open flame. Do not smoke or ignite matches, lighters, etc. For industrial or professional use only.

### 7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed. Store away from oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide local exhaust ventilation at transfer points. Provide appropriate local exhaust ventilation on open containers. If exhaust ventilation is not available, use appropriate respiratory protection.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Indirect Vented Goggles.

#### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Butyl Rubber, Polyethylene/Ethylene Vinyl Alcohol.

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with

OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

### 8.3 EXPOSURE GUIDELINES

<u><b>Ingredient</b></u>	<u><b>Authority</b></u>	<u><b>Type</b></u>	<u><b>Limit</b></u>	<u><b>Additional Information</b></u>
Acetone	ACGIH	TWA	500 ppm	Table A4
Acetone	ACGIH	STEL	750 ppm	Table A4
Acetone	OSHA	TWA, Vacated	750 ppm	
Acetone	OSHA	TWA	1000 ppm	Table Z-1
Acetone	OSHA	STEL, Vacated	1000 ppm	
Cyclohexane	ACGIH	TWA	100 ppm	
Cyclohexane	OSHA	TWA	300 ppm	Table Z-1
n-Hexane	ACGIH	TWA	50 ppm	Skin Notation*
n-Hexane	OSHA	TWA, Vacated	50 ppm	Table Z-1A
n-Hexane	OSHA	TWA	500 ppm	Table Z-1A
Toluene	ACGIH	TWA	50 ppm	Skin Notation*; Table A4
Toluene	CMRG	STEL	75 ppm	Skin Notation*
Toluene	OSHA	TWA, Vacated	100 ppm	
Toluene	OSHA	STEL, Vacated	150 ppm	
Toluene	OSHA	TWA	200 ppm	Table Z-2
Toluene	OSHA	CEIL	300 ppm	Table Z-2
Zinc Oxide	ACGIH	TWA, respirable	2 mg/m3	
Zinc Oxide	ACGIH	STEL	10 mg/m3	
Zinc Oxide	OSHA	TWA, as fume	5 mg/m3	Table Z-1
Zinc Oxide	OSHA	TWA, respirable	5 mg/m3	Table Z-1
Zinc Oxide	OSHA	STEL, Vacated, as fume	10 mg/m3	
Zinc Oxide	OSHA	TWA, Vacated, as dust	10 mg/m3	
Zinc Oxide	OSHA	TWA, as total dust	15 mg/m3	Table Z-1

\* Substance(s) refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

VAC Vacated PEL: Vacated Permissible Exposure Limits [PEL] are enforced as the OSHA PEL in some states. Check with your local regulatory agency.

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Odor, Color, Grade:**

yellow, solvent odor.

**General Physical Form:**

Liquid

**Autoignition temperature**

465 °C [Details: Acetone]

**Flash Point**

-4 °F [Test Method: Closed Cup] [Details: Acetone]

**Flammable Limits - LEL**

1.0 % volume

**Flammable Limits - UEL**

12.8 % volume

Boiling point	>=56 °C [Details: Acetone]
Density	0.83 g/ml
Vapor Density	2.0 [Ref Std: AIR=1]
Vapor Pressure	<=185 mmHg [@ 68 °F]
Specific Gravity	0.83 [Ref Std: WATER=1]
pH	Not Applicable
Melting point	Not Applicable
Solubility in Water	Nil
Evaporation rate	>=2.0 [Ref Std: ETHER=1]
Hazardous Air Pollutants	22 % weight [Test Method: Calculated] [Details: 1.0 lb. HAPS/lbs. Solids]
Volatile Organic Compounds	422 g/l [Test Method: calculated SCAQMD rule 443.1]
Percent volatile	70 - 80 % weight
VOC Less H2O & Exempt Solvents	584 g/l [Test Method: calculated SCAQMD rule 443.1]
Viscosity	450 - 700 centipoise [@ 73.4 °F]

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

**Materials and Conditions to Avoid:** Strong oxidizing agents; Heat; Sparks and/or flames

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products

#### Substance

Hydrocarbons  
Carbon monoxide  
Carbon dioxide

#### Condition

During Combustion  
During Combustion  
During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Dispose of completely cured (or polymerized) wastes in a sanitary landfill. Incinerate uncured product in a permitted hazardous waste incinerator.  
As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.  
Combustion products will include HCl. Facility must be capable of handling halogenated materials.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

**SECTION 14: TRANSPORT INFORMATION****ID Number(s):**

62-2166-5320-4, 62-2166-5520-9, 62-2166-6520-8, 62-2166-6530-7, 62-2166-7520-7, 62-2166-8520-6, 62-2166-9520-5, 62-2166-9535-3

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

**SECTION 15: REGULATORY INFORMATION****US FEDERAL REGULATIONS**

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
n-Hexane	110-54-3	10 - 30
Toluene	108-88-3	10 - 30
Cyclohexane	110-82-7	1 - 5

**This material contains a chemical which requires export notification under TSCA Section 12[b]:**

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
n-Hexane	110-54-3	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
Cyclohexane	110-82-7	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
Acetone	67-64-1	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

**STATE REGULATIONS**

Contact 3M for more information.

**CALIFORNIA PROPOSITION 65****Ingredient**

Toluene

**C.A.S. No.**

108-88-3

**Classification**

\*Developmental Toxin

\* WARNING: contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**CHEMICAL INVENTORIES**

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

**INTERNATIONAL REGULATIONS**

Contact 3M for more information.

**WHMIS:** Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**SECTION 16: OTHER INFORMATION****NFPA Hazard Classification**

**Health:** 2 **Flammability:** 3 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:**

Section 1: Product name was modified.

Section 1: Product use information was modified.

Section 16: NFPA hazard classification heading was modified.

Section 3: Other potential health effects heading was modified.

Section 1: Division name was modified.

Copyright was modified.



Section 8: Exposure guidelines data source legend was modified.  
Section 4: First aid for eye contact - decontamination - was modified.  
Section 4: First aid for eye contact - medical assistance - was modified.  
Section 3: Immediate physical hazard(s) was modified.  
Section 3: Potential effects from eye contact was modified.  
Section 3: Potential effects from skin contact information was modified.  
Section 3: Potential effects from inhalation information was modified.  
Section 3: Potential effects from ingestion information was modified.  
Section 5: Fire fighting procedures information was modified.  
Section 5: Unusual fire and explosion hazard information was modified.  
Section 6: Release measures information was modified.  
Section 7: Handling information was modified.  
Section 7: Storage information was modified.  
Section 8: Engineering controls information was modified.  
Section 8: Eye/face protection phrase was modified.  
Section 8: Skin protection phrase was modified.  
Section 10: Hazardous decomposition or by-products table was modified.  
Section 13: Waste disposal method information was modified.  
Section 8: Eye/face protection information was modified.  
Section 8: Skin protection - recommended gloves information was modified.  
Section 15: 311/312 hazard categories heading was modified.  
Section 15: International regulations information was modified.  
Section 15: State regulations information was modified.  
Section 15: US federal regulations information was modified.  
Section 4: First aid for skin contact - decontamination - was modified.  
Section 4: First aid for skin contact - medical assistance - was modified.  
Section 4: First aid for ingestion (swallowing) - decontamination - was modified.  
Section 4: First aid for ingestion (swallowing) - medical assistance - was modified.  
Section 10: Hazardous polymerization heading was modified.  
Section 10: Materials and conditions to avoid physical property was modified.  
Section 2: Ingredient table was modified.  
Section 15: TSCA section 12[b] text was modified.  
Section 3: Other health effects information was modified.  
Section 16: NFPA explanation was modified.  
Page Heading: Product name was modified.  
Section 15: Inventories information was modified.  
Section 15: EPCRA 313 information was modified.  
Section 15: California proposition 65 ingredient information was modified.  
Section 15: EPCRA 313 text was modified.  
Section 15: California proposition 65 heading was modified.  
Section 15: California proposition 65 reproductive harm warning was modified.  
Section 12: Ecotoxicological information heading was modified.  
Section 12: Chemical fate information heading was modified.  
Section 8: Exposure guidelines ingredient information was modified.  
Section 8: Exposure guidelines legend was modified.  
Section 8: Exposure guideline note was modified.  
Section 9: Vapor density value was modified.  
Section 9: Vapor pressure value was modified.  
Section 9: Boiling point information was modified.  
Section 5: Flammable limits (UE) information was modified.  
Section 5: Flammable limits (LEL) information was modified.  
Section 5: Autoignition temperature information was modified.  
Section 5: Flash point information was modified.  
Section 9: Property description for optional properties was modified.  
Section 9: Specific gravity information was modified.  
Section 9: pH information was modified.

Section 9: Melting point information was modified.  
Section 16: NFPA hazard classification for special hazards was modified.  
Section 9: Flash point information was modified.  
Section 9: Flammable limits (LEL) information was modified.  
Section 9: Flammable limits (UEL) information was modified.  
Section 9: Autoignition temperature information was modified.  
Section 15: TSCA section 12[b] information was modified.  
Section 3: Other health effects information (reproductive hazards) was modified.  
Section 5: OSHA flammability heading was added.  
Section 5: OSHA flammability data was added.  
Section 3: Immediate eye hazard(s) was added.  
Section 15: WHMIS regulations heading was added.  
Section 15: WHMIS regulations information was added.  
Section 4: First aid for skin contact - termination of exposure - was added.  
Section 4: First aid for skin contact - handling - was added.  
Section 9: Density information was added.  
Section 9: Solubility in water text was added.  
Section 2: Ingredient phrase was added.  
Section 12: Ecotoxicological phrase was added.  
Section 12: Chemical Fate phrase was added.  
Section 7: Handling comment was deleted.  
Section 15: Ingredient comment heading was deleted.  
Section 15: Inventories comment was deleted.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M MSDSs are available at [www.3M.com](http://www.3M.com)**